

Cruiser/Touring/Custom

Venom

- Low noise levels
- Excellent cornering stability
- Reinforced fitments available for bikes carrying heavy loads
- Availability of whitewalls in some sizes

Venom specification

Code	Tyre Size	Service Index	Rec Rim	Rim min-max	Overall Width mm/inches	Overall Diameter mm/inches	Depth mm	Revs per km/mile
Venom AM41 Front								
2808012	80/90-21	48H	MT1.85	1.60 - 2.15	83 / 3.3	688 / 27.1	5.2	479 / 766.4
2808112	90/90-21	54H	2.15	1.85 - 2.50	94 / 3.7	701 / 27.6	5.2	468 / 748.8
2806912	100/90-18	56H	MT2.50	2.15 - 2.75	107 / 4.2	638 / 25.1	5.2	520 / 832.0
2809012	100/90-19	57H	MT2.50	2.15 - 2.75	109 / 4.3	662 / 26.1	5.2	500 / 800.0
2809019	100/90-19 _{ww}	57H	MT2.50	2.15 - 2.75	110 / 4.3	662 / 26.1	5.2	500 / 800.0
2809612	110/90-19	62H	MT2.50	2.15 - 3.00	119 / 4.7	682 / 26.9	5.2	487 / 779.2
2806012	120/90-18*	71H	MT2.75	2.50 - 3.00	129 / 5.1	674 / 26.5	5.2	496 / 793.6
2800091	120/70-21*	68H	MT3.50	2.75 - 3.75	120 / 4.7	709 / 27.9	4.8	467 / 747.3
2804112	120/70-21	62H	MT3.50	2.75 - 3.75	120 / 4.7	709 / 27.9	4.8	467 / 747.3
2806612	130/70B18*	69H	MT3.50	3.00 - 4.00	130 / 5.1	647 / 25.5	4.7	513 / 820.8
2809713	140/70B18	67V	MT3.75	3.50 - 4.50	139 / 5.5	658 / 25.9	4.7	503 / 805.0
2807412	150/80-16	71H	MT3.50	3.00 - 4.25	157 / 6.2	637 / 25.1	5.2	525 / 840.0
2809312	MH90-21*	56H	1.85	1.60 - 2.15	83 / 3.3	688 / 27.1	5.2	479 / 766.4
2809319	MH90-21 _{ww} *	56H	1.85	1.60 - 2.15	83 / 3.3	686 / 27.0	5.2	479 / 766.4
2805012	MT90B16*	74H	3.00D	2.50 - 3.50	136 / 5.4	638 / 25.1	5.2	523 / 836.8
2805017	MT90B16 _{ww} *	74H	3.00D	2.50 - 3.50	136 / 5.4	638 / 25.1	5.2	523 / 836.8
2805019	MT90B16 _{ww} *	74H	3.00D	2.50 - 3.50	136 / 5.4	638 / 25.1	5.2	523 / 836.8

Venom AM41 Rear								
2848712	140/90B16	77H	MT3.50	2.75 - 3.75	143 / 5.6	649 / 25.6	8.7	518 / 828.8
2848719	140/90B16 _{ww}	77H	MT3.50	2.75 - 3.75	143 / 5.6	649 / 25.6	8.7	518 / 828.8
2844412	140/90-15	76H	MT3.50	2.75 - 3.75	149 / 5.9	633 / 24.9	8.7	530 / 848.0
2847493	150/80B16	77V	MT3.50	3.00 - 4.25	157 / 6.2	640 / 25.2	7.2	518 / 828.8
2847492	150/80B16	77H	MT3.50	3.00 - 4.25	150 / 5.9	641 / 25.2	8.7	518 / 828.8
2957412	150/80B16 _{ww}	77V	MT3.50	3.00 - 4.25	157 / 6.2	641 / 25.2	7.2	518 / 828.8
2848912	150/90B15*	80H	MT3.50	3.00 - 4.25	159 / 6.3	645 / 25.4	8.7	523 / 836.8
2848913	150/90B15 (74V)	76V	MT3.50	3.00 - 4.25	159 / 6.3	645 / 25.4	8.7	523 / 836.8
2950091	150/70B18*	76V	MT4.25	3.50 - 4.50	148 / 5.8	665 / 26.2	5.7	498 / 796.7
2846513	150/70B18	70V	MT4.25	3.50 - 4.50	148 / 5.8	665 / 26.2	5.7	498 / 796.7
2844912	160/80B16*	81H	MT4.00	3.50 - 4.50	167 / 6.6	665 / 26.2	8.7	505 / 808.0
2844512	170/80B15*	83H	MT4.00	3.50 - 4.50	176 / 6.9	659 / 25.9	8.7	512 / 819.2
2843712	200/70-15*	82H	MT5.5	4.75 - 6.25	203 / 8.0	665 / 26.2	7.7	505 / 808.0
2845012	MT90B16*	74H	3.00D	2.50 - 3.50	133 / 5.2	638 / 25.1	8.7	522 / 835.2
2845017	MT90B16 _{ww} *	74H	3.00D	2.50 - 3.50	131 / 5.2	640 / 25.2	8.7	522 / 835.2
2845019	MT90B16 _{ww} *	74H	3.00D	2.50 - 3.50	134 / 5.3	639 / 25.2	8.7	522 / 835.2

WW – Wide White Wall.
 NW – Narrow White Wall.
 *Reinforced.
 MT90-16 replaces 130/90-16.
 140/90B16 replaces MU85B16.

